

Some references



D. Boffi

Finite element approximation of eigenvalue problems
Acta Numerica 19 (2010), 1–120



D. Boffi, F. Gardini, and L. Gastaldi

Some remarks on eigenvalue approximation by finite elements
In *Frontiers in Numerical Analysis – Durham 2010*, Springer
Lecture Notes in Computational Science and Engineering, 85
(2012), 1–77



D. Boffi, F. Brezzi, and M. Fortin

Mixed Finite Element Methods and Applications
Springer Series in Computational Mathematics, Vol. 44, 2013

The classical electromagnetic field is described by the four vectors \mathcal{E} , \mathcal{D} , \mathcal{H} , and \mathcal{B} which are functions of the position $\mathbf{x} \in \mathbb{R}^3$ and of the time $t \in \mathbb{R}$. The vectors \mathcal{E} and \mathcal{H} are referred to as the electric and magnetic field, while \mathcal{D} and \mathcal{B} are the electric and magnetic displacements, respectively.

The Faraday law of induction states

$$\int_{\partial\Sigma} \mathcal{E} \cdot ds = -\frac{d}{dt} \int_{\Sigma} \mathcal{B} \cdot \mathbf{n}$$

The Ampère law says

$$\int_{\partial\Sigma} \mathcal{H} \cdot ds = \frac{d}{dt} \int_{\Sigma} \mathcal{D} \cdot \mathbf{n} + \int_{\Sigma} \mathcal{J} \cdot \mathbf{n}$$

where \mathcal{J} denotes the current density vector.

It can be noticed that the fields \mathcal{E} , \mathcal{H} , \mathcal{B} , and \mathcal{D} have a different nature. Indeed, the first two are integral 1-forms, while the latter two are integral 2-forms.

This remark is of fundamental importance for the design of finite element schemes.

It can be noticed that the fields \mathcal{E} , \mathcal{H} , \mathcal{B} , and \mathcal{D} have a different nature. Indeed, the first two are integral 1-forms, while the latter two are integral 2-forms.

This remark is of fundamental importance for the design of finite element schemes.

The differential forms of Faraday and Ampère laws read

$$\begin{aligned}\frac{\partial \mathcal{B}}{\partial t} + \mathbf{curl} \mathcal{E} &= 0 \\ \frac{\partial \mathcal{D}}{\partial t} - \mathbf{curl} \mathcal{H} &= -\mathcal{J}\end{aligned}$$

It can be noticed that the fields \mathcal{E} , \mathcal{H} , \mathcal{B} , and \mathcal{D} have a different nature. Indeed, the first two are integral 1-forms, while the latter two are integral 2-forms.

This remark is of fundamental importance for the design of finite element schemes.

The differential forms of Faraday and Ampère laws read

$$\begin{aligned}\frac{\partial \mathcal{B}}{\partial t} + \mathbf{curl} \mathcal{E} &= 0 \\ \frac{\partial \mathcal{D}}{\partial t} - \mathbf{curl} \mathcal{H} &= -\mathcal{J}\end{aligned}$$

which are usually referred to as Maxwell's equations, together with the two Gauss Laws

$$\begin{aligned}\operatorname{div} \mathcal{D} &= \rho \\ \operatorname{div} \mathcal{B} &= 0\end{aligned}$$

where ρ denotes the charge density function.

The time-harmonic Maxwell system is considered, for instance, when the Fourier transform in time is used or when the propagation of electromagnetic waves at a given frequency is studied. Then, given a frequency ω , we consider the *ansatz*:

$$\mathcal{E}(\mathbf{x}, t) = \Re \left(e^{-i\omega t} \mathbf{E}(\mathbf{x}) \right)$$

$$\mathcal{D}(\mathbf{x}, t) = \Re \left(e^{-i\omega t} \mathbf{D}(\mathbf{x}) \right)$$

$$\mathcal{H}(\mathbf{x}, t) = \Re \left(e^{-i\omega t} \mathbf{H}(\mathbf{x}) \right)$$

$$\mathcal{B}(\mathbf{x}, t) = \Re \left(e^{-i\omega t} \mathbf{B}(\mathbf{x}) \right)$$

where \Re denotes the *real part*. We define also

$$\mathcal{J}(\mathbf{x}, t) = \Re \left(e^{-i\omega t} \mathbf{J}(\mathbf{x}) \right)$$

$$\rho(\mathbf{x}, t) = \Re \left(e^{-i\omega t} r(\mathbf{x}) \right)$$

Standard constitutive equations for linear media read

$$\mathbf{D} = \varepsilon \mathbf{E} \quad \mathbf{B} = \mu \mathbf{H}$$

where ε and μ denote the electric permittivity and the magnetic permeability, respectively. For general inhomogeneous, anisotropic materials ε and μ are 3×3 positive definite matrix functions.

Standard constitutive equations for linear media read

$$\mathbf{D} = \varepsilon \mathbf{E} \quad \mathbf{B} = \mu \mathbf{H}$$

where ε and μ denote the electric permittivity and the magnetic permeability, respectively. For general inhomogeneous, anisotropic materials ε and μ are 3×3 positive definite matrix functions. Inserting constitutive relations into the Maxwell's equations and considering the time-harmonic assumptions, we get the time harmonic Maxwell's equations

$$\mathbf{curl} \mathbf{E} - i\omega\mu\mathbf{H} = \mathbf{0}$$

$$\mathbf{div}(\varepsilon\mathbf{E}) = r$$

$$\mathbf{curl} \mathbf{H} + i\omega\varepsilon\mathbf{E} = \mathbf{J}$$

$$\mathbf{div}(\mu\mathbf{H}) = 0$$

It is a standard procedure to eliminate one variable and to write the time harmonic Maxwell's system as a second order system. Eliminating for instance the field \mathbf{H} , we get

$$\mathbf{curl}(\mu^{-1} \mathbf{curl} \mathbf{E}) - \omega^2 \varepsilon \mathbf{E} = \mathbf{F}$$

where \mathbf{F} is given by $i\omega\mathbf{J}$, together with the divergence condition (which follows from the equation)

$$-\omega^2 \operatorname{div}(\varepsilon \mathbf{E}) = \operatorname{div} \mathbf{F}.$$

It is a standard procedure to eliminate one variable and to write the time harmonic Maxwell's system as a second order system. Eliminating for instance the field \mathbf{H} , we get

$$\mathbf{curl}(\mu^{-1} \mathbf{curl} \mathbf{E}) - \omega^2 \varepsilon \mathbf{E} = \mathbf{F}$$

where \mathbf{F} is given by $i\omega\mathbf{J}$, together with the divergence condition (which follows from the equation)

$$-\omega^2 \operatorname{div}(\varepsilon \mathbf{E}) = \operatorname{div} \mathbf{F}.$$

The equation is usually equipped with suitable boundary conditions. The simplest one is the perfect conducting boundary condition which reads

$$\mathbf{E} \times \mathbf{n} = 0$$

where \mathbf{n} is the outward unit vector.